

Марка вентилятора	конструктивное исполнение	Частота вращения, об/мин.	L _{pA} , дБА
BP 80-75 №2,5	схема 1	1500	67
		3000	84
BP 80-75 №3,15	схема 1	1500	74
		3000	92
BP 80-75 №4	схема 1	1000	73
		1500	82
		3000	101
BP 80-75 №5	схема 1	1000	78
		1500	89
BP 80-75 №6,3	схема 1	1000	86
		1500	97
BP 80-75 №8	схема 1	1000	96
BP 80-75 №8	схема 5	1500	95
BP 80-75 №10	схема 1	750	90
		1000	99
BP 80-75 №10	схема 5	615	86
		685	89
		770	91
		865	94
BP 80-75 №12,5	схема 1	750	97
BP 80-75 №12,5	схема 5	536	90
		602	93
		685	97
		768	99

Марка вентилятора	Значение L _p в октавных полосах f, Гц							
	63	125	250	500	1000	2000	4000	8000
BP 80-75 №2,5	58	61	69	62	60	58	50	41
	72	73	76	84	77	75	73	65
BP 80-75 №3,15	66	68	76	69	67	65	57	48
	79	81	84	92	85	83	81	73
BP 80-75 №4	66	68	76	69	67	65	57	46
	75	77	85	78	76	74	66	57
	89	90	93	101	94	92	90	82
BP 80-75 №5	71	73	81	71	72	70	62	53
	80	84	92	85	83	81	73	64
BP 80-75 №6,3	79	81	89	82	80	73	70	61
	90	92	100	93	91	89	81	72
BP 80-75 №8	89	91	99	92	90	88	80	71
BP 80-75 №8	90	92	98	95	92	90	83	74

BP 80-75 №10	91	94	90	88	85	80	73	64
	92	95	100	96	94	91	86	79
BP 80-75 №10	88	90	86	84	81	76	69	60
	91	93	89	87	84	79	72	63
	93	95	91	89	86	81	74	63
	95	98	94	92	89	84	77	68
BP 80-75 №12,5	98	101	97	95	92	87	80	71
BP 80-75 №12,5	91	94	90	88	85	80	73	64
	95	97	93	91	88	83	76	67
	97	100	96	94	91	86	79	70
	99	102	98	96	93	88	81	72